

eurotech
fire systems limited

euro-fi[®]

EUW-BS-05

Wireless base sounder



Product Summary

The EUW-BS-05 Wireless Sounder Base unit is an aesthetically pleasing and cost effective alternative to traditional wall mounted sounder units where visual impact is important. Each unit has an integral moulded base for mounting a Euro-fi wireless detector or a sounder cover if a detector is not required. The unit has as standard 32 recognised sounder tones and 3 levels of volume adjustment, all of which can be easily configured on site.

Powered by standard lithium batteries and utilising well proven adaptive radio signal processing algorithms ensure the highest levels of life safety and reliability.

Key Features

- 3rd party approval to EN54-25 and EN54-03
- Bi-directional wireless communication
- 5 year product warranty
- Utilises dual low-cost standard lithium batteries
- Choice of 32 recognised tones
- Compatible with all Euro-fi translators and expanders
- Integral detector base
- Red and white cover options
- 3 volume levels
- 3 year expected battery life

Standards & Approvals

BS EN 54-3:
Fire alarm devices

BS EN 54-25:
Components using radio links and system requirements



Technical Specification

• Operating frequency range	868 - 870 MHz
• Operating frequency channels	7
• Communication range with the translator or expander	≤ 150m (in open space)
• IP rating	20 (type A for indoor use only)
• Sound output (typical)	70-95 dBA (tone dependant)
• Number of tones	32
• Dimensions	16mm x 51mm
• Weight (without batteries)	150g
• Primary battery	CR123A (3V & 1.2 Ah)
• Secondary battery	CR123A (3V & 1.2 Ah)
• Primary battery lifespan (typical)	≥ 3 years
• Secondary battery lifespan (typical)	≥ 2 months
• Operating temperature	-10°C to +55°C
• Max humidity (non condensing)	95% RH

